

SCOT PUMP

DIVISION OF ARDOX CORP.

MODEL CG-P5B

200 GPM — 5 HP

De-Watering Pump



DIMENSIONS
20.5"L x 14.5"W x 17.75"H



FLASHLIGHT



SUCTION HOSE



DISCHARGE HOSE



EXTRA
REFUELING TANK



ALUMINUM CONTAINER
(Optional)



ADJUSTABLE FIRE NOZZLE & HOSE
(Optional)

- Lightweight Pump and Engine
Weighs Only 65 pounds (without hoses)
- Aluminum Construction, Hard Coated
For Sea or Fresh Water Duty
- 200 Gallons per Minute with 10 ft. Suction Lift
- 30 Second Quick Prime® Design
- Aluminum shutoff/throttling valve
- 2-1/2 inch x 15 foot Suction Hose with
Stainless Steel Strainer
- 3 inch x 20 foot Discharge Hose
for de-watering rate of 12,000 gallons per hour
- Glass Filled Nylon Quick Disconnect
Hose Fittings
- 5 HP Briggs & Stratton Recoil Start "Industrial Plus"
Gasoline Engine.
- Coast Guard Approved Flashlight
- (2) each refueling tanks with automatic 2-way vent
valves (3.5 hours of operation)
- Stainless Steel Carrying Cradle designed for
two-hand pickup
- 2 inch x 50 ft. fire hose with adjustable nozzle
for fire fighting and washdown. (Optional)
Rated 50 GPM at 40 PSI
P/N 118.000.480A
- Aluminum Storage Container (Optional)
Water Tight Construction
24 inch Dia. x 24 inch Ht. - Wt. 21 pounds
P/N 119.000.223X
- Weight
Pump and Hoses — 83 pounds
- Weight
Container, Pump, Hoses, and Refueling Tanks
120 pounds
- **NOTE:** All weights are without fuel

81.001.558

CG-P5B

DE-WATERING PUMP

AUG 2000

SCOT